

SlipNOT® Specifications

SlipNOT® Specifications for Grade 3:

STEEL

SlipNOT®, grit-free, steel Grip Plate® / Grip Grate® Grade #3 – Coarse, as manufactured by the W.S. Molnar Company (1-800-SlipNOT) is available in stock sizes or manufactured to detailed specifications on drawings. Steel Grip Plate® / Grip Grate® shall incorporate an anti-slip primarily martensitic steel surface covering 100% of the substrate consisting of a random hatch matrix with a surface hardness between 55 – 63 on the Rockwell “C” scale and a bond strength of the Steel Grip Plate® / Grip Grate® of at least 4,000 psi. The non-slip surface shall have a minimum coefficient of friction of 0.8 and be listed as slip resistant by Underwriters Laboratories.



DIVISION OF THE W.S. MOLNAR COMPANY

For more information, please contact us at:

2545 Beaufait Street | Detroit, MI 48207

Phone: (313) 923-0400 | Fax: (313) 923-4555

www.slipnot.com | info@slipnot.com | 1-800-SlipNOT

SlipNOT® Metal Safety Flooring products may be covered by one or more of the following patents; 5,711,119, 6,839,951 and 6,863,932.

© Copyright 2011 W.S. Molnar. All rights reserved.